



## Emerald

A modern and flexible spotlight, perfect for showing landscapes in an entirely new light



5W	10W
Measurements (mm)	Measurements (mm)
Absolute Luminous Flux	Absolute Luminous Flux
5W (24V DC) 319lm (at 3000K) 341lm (at 4000K)	10W (24V DC) 865lm (at 3000K) 922lm (at 4000K)
Beam	Beam
15° (P)   24° (N)   38° (M)	15° (P)   24° (N)   38° (M)

### Finishes

UV Textured Black



UV Textured Grey



### General Specifications

Material	Powder Coated Aluminium, PVC Spike
IP	65
Cable Length	500mm
Wiring	Wired in Parallel
Warranty	3 Years

### LED

Colour Temp	3000K, 4000K
CRI (Ra/R9)	80+ / >0
Efficacy	Up to 71lm/W
Colour Deviation	SDCM ≤ 3
Lifetime	5W: >60,000h L80B10 10W: >50,000h L70B10

### Driver

24V DC Remote Non-Dimmable Driver (CV2)



## Spike Spotlight

**NEW** Spotlight Shroud for glare control

Available in two sizes – 5W and 10W

Designed with a detachable spike for optional surface mounted applications


Ideal for garden beds, plants and tall trees

### Accessories




Spotlight Shroud


### Beam Options



Pencil | 12° (P)



Narrow | 24° (N)



Medium | 36° (M)