





Ovo

Wall Light

Cast a round, ambient glow for stairwells, entryways and corridors



Measurements (mm)	
Luminaire	Wallbox
	
Ø 85 (Ø 68)	Ø 74 (Ø 75)
Absolute Luminous Flux	
2W (700mA) 95lm (at 3000K)	
Beam	
120° (F)	

Finishes	
UV Textured Black	
UV Textured White	


General Specifications	
Material	Powder Coated Aluminium, PVC Wallbox
IP	65
Wiring	Wired in Series
Warranty	3 Years

LED	
Colour Temp	3000K, 4000K
CRI (Ra/R9)	80+ / >0
Efficacy	Up to 30lm/W
Colour Deviation	SDCM ≤ 3
Lifetime	> 60,000h L80B10

Driver	
240V Remote Non-Dimmable Driver	
240V Remote Osram DALI Driver (OD) <sup>1</sup>	
240V Remote Tridonic basicDIM Bluetooth Driver (TB) <sup>1</sup>	



- Striking circular concave design
- Produces a unique circular beam on surfaces
- Complete with tension wing clips (suitable with or without wallbox installations)



**Notes**  
<sup>1</sup>Ovo Wall Light must be installed in groups of 3+ for Osram DALI and 5+ for basicDIM Bluetooth driver options. Please contact sales@unios.com for more information.