







Helix

Wall Light

A uniquely adjustable vanity luminaire for direct and indirect lighting applications

	
Single Arm	Twin Arm
Measurements (mm)	Measurements (mm)
	
Absolute Luminous Flux	Absolute Luminous Flux
5W (400mA) 405lm (at 3000K) 410lm (at 4000K)	10W (400mA) 745lm (3000K) 825lm (4000K)
Beam	Beam
90° (F)	90° (F)

Finishes	
Textured Black	
Textured White	

General Specifications	
Material	Powder Coated Aluminium, Frosted Acrylic Diffuser
IP	44
Warranty	3 Years

LED	
Colour Temp	3000K, 4000K
CRI (Ra/R9)	90+ / >50
Efficacy	Up to 64lm/W
Colour Deviation	SDCM≤3
Lifetime	>50,000h L70B10

Driver	
240V Built-in Non-Dimmable Driver	
240V Remote Tridonic one4all DALI Driver (TD)	
240V Remote Tridonic basicDIM Bluetooth Driver (TB)*	




Ideal for vanity applications and feature corridor lighting

180° in each arm for gentle indirect or direct light (when rotated outwards)

Excellent colour rendering with a CRI rating of 90+

Suitable for horizontal and vertical applications

Available in single or double arm configurations



Notes
Helix Wall Light requires 30mm of clearance from the mounting surface throughout its full rotation range.
*Helix Single must be installed in pairs when using the basicDIM Bluetooth driver.