




Iris

Wall Light

A gentle halo of light to accentuate architectural spaces

Small	Medium	Large
Measurements (mm)	Measurements (mm)	Measurements (mm)
 Ø 120 50	 Ø 225 50	 Ø 350 50
Absolute Luminous Flux	Absolute Luminous Flux	Absolute Luminous Flux
5W (350mA) 217lm (at 3000K)	8W (300mA) 656lm (at 3000K)	15W (500mA) 824lm (at 3000K)
Beam	Beam	Beam
100° (W)	100° (W)	100° (W)

Finishes

UV Textured Black
UV Textured White

General Specifications

Material Powder Coated Aluminium
IP Small, Medium: IP65
Large: IP20
Warranty 5 Years

LED

Colour Temp 3000K, 4000K
CRI (Ra/R9) 90+ / >50
Efficacy Up to 66lm/W
Colour Deviation SDCM ≤ 3
Lifetime >50,000h L70B10

Driver

240V Built-in Phase-Cut Dimmable Driver
240V Built-in Tridonic one4all DALI Driver (TD)¹
240V Built-in Tridonic basicDIM Bluetooth Driver (TB)¹



Three distinct sizes (120mm, 225mm and 350mm)

Can be installed individually or in clusters

Small and medium sizes are IP65

Medium and large versions are compatible with a DALI integral driver

Beam Options



Flood | 100° (W)

Notes

¹Small model requires Tridonic drivers to be installed remotely due to size constraints.