



Kobe

Track Light Series

The adaptable and versatile track light

Distinguished by a striking contrasting design, the Kobe Track Light Series will add an elegant touch to any design application. Designed with universal use and application variety in mind, the Kobe Series has been introduced throughout a spectrum of residential and commercial projects. As a spotlight for highlighting objects and surfaces
















in retail applications, the Kobe Series delivers a precise and practical solution. As a general lighting solution, the Kobe Series offers a more flexible alternative to traditional downlight scenarios. This track light is available in four meticulously selected finishes and a horticultural version – perfect for greenscapes and indoor plants.




Kobe


Track Light Series




8W	15W	26W	35W
Measurements (mm)	Measurements (mm)	Measurements (mm)	Measurements (mm)
 147	 160	 170	 188
Absolute Luminous Flux	Absolute Luminous Flux	Absolute Luminous Flux	Absolute Luminous Flux
8W (200mA) 735lm (at 3000K) 752lm (at 4000K)	15W (380mA) 1311lm (at 3000K) 1492lm (at 4000K)	26W (670mA) 2301lm (at 3000K) 2437lm (at 4000K)	35W (900mA) 3357lm (at 3000K) 3458lm (at 4000K)
Beam	Beam	Flo Horticulture ¹	Beam
15° (P) 36° (M) 60° (W)	15° (P) 36° (M) 60° (W)	26W (700mA) 1815lm (at 2400K)	15° (P) 36° (M) 60° (W)
Weight	Weight	Beam	Weight
0.72kg	0.83kg	15° (P) 36° (M) 60° (W)	1.62kg
Finishes			
Textured Black			
White/Black Trim			
Black/Gold Trim			
White/Gold Trim			
General Specifications			
Material	Powder Coated Aluminium		
Track Mount	Three (3C) Circuit, Single (1C) Circuit		
UGR (Unified Glare Rating)	<13		
IP	20		
Warranty	5 Years		
LED			
Colour Temp	2400K (Horticulture) ¹ , 2700K, 3000K, 4000K		
CRI (Ra/R9)	92+ />50, 97+ />90 ²		
Efficacy	Up to 92lm/W		
Colour Deviation	SDCM≤2		
Lifetime	>55,000h L80B10		
PPF (Flo series)	Typical (43.2 umol/sec)		
Active-PPF (Flo series)	Typical (29.1 umol/sec)		
Driver			
240V Built-in Phase-Cut Dimmable Driver			
240V Track Adaptor Gearbox Tridonic one4all DALI Driver (TD)			
240V Track Adaptor Gearbox Tridonic basicDIM Bluetooth Driver (TB)			
Notes			
¹ Flo horticulture series is only available in a 26W variation. Higher output options available upon request.			
² For CRI 97+ lumen outputs, please refer to the values on the Unios Toolbox.			
      			


Accessories



Linear Lens


Honeycomb Lens


Beam Options


Pencil | 15° (P)


Medium | 36° (M)


Wide | 60° (W)

Product Collection


Kobe Spotlight Series
Page 98



The most adaptable of track light solutions is presented in the Kobe Track Light. Suitable for both commercial and residential applications, this luminaire will offer a functional and ideal lighting solution and meet the demands of any project requirement.

Complete customisability

The Kobe Track Light comes available in four meticulously selected finishes, an array of customisable configurations and multiple beam angles and lenses to complement any application.

Unmatched colour rendering

In applications where colour rendering is of paramount importance and light quality cannot be compromised, the Kobe Track Light is available in 97+ CRI.

An extended lifetime

Class-leading longevity is a promise in the Kobe Track Light with new generation LED chips. These LED chips now allow for a lifetime of over 60,000h (L80B10).













Horticultural technology





The Flo Series combines our expertise in architectural lighting with innovative horticulture technology. Unios have incorporated this LED module with the Kobe luminaire design.





Kobe

			
8W	15W	26W	35W
Measurements (mm)	Measurements (mm)	Measurements (mm)	Measurements (mm)
Surface Mounted	Surface Mounted	Surface Mounted	Surface Mounted
 Ø 74	 Ø 74	 Ø 104	 Ø 105
Recessed	Recessed	Recessed	Recessed
 Ø 74	 Ø 74	 Ø 105	 Ø 105
Absolute Luminous Flux	Absolute Luminous Flux	Absolute Luminous Flux	Absolute Luminous Flux
8W (200mA) 735lm (at 3000K) 752lm (at 4000K)	15W (380mA) 1311lm (at 3000K) 1492lm (at 4000K)	26W (670mA) 2301lm (at 3000K) 2437lm (at 4000K)	35W (900mA) 3357lm (at 3000K) 3458lm (at 4000K)
Beam	Beam	Flo 26W (700mA) 1815lm (at 2400K)	Beam
15° (P) 36° (M) 60° (W)	15° (P) 36° (M) 60° (W)	15° (P) 36° (M) 60° (W)	15° (P) 36° (M) 60° (W)

Finishes	
Textured Black	
White/Black Trim	
Black/Gold Trim	
White/Gold Trim	

General Specifications	
Material	Powder Coated Aluminium
UGR (Unified Glare Rating)	<13
IP	20
Warranty	5 Years

LED	
Colour Temp	2400K (Horticulture) ¹ , 2700K, 3000K, 4000K
CRI (Ra/R9)	92+/ ² >50, 97+/ ² >90 ²
Efficacy	Up to 92lm/W
Colour Deviation	SDCM≤2
Lifetime	>55,000h L80B10
PPF (Flo series)	Typical (43.2 umol/sec)
Active-PPF (Flo series)	Typical (29.1 umol/sec)







Driver
240V Built-in Phase-Cut Dimmable Driver
240V Remote Tridonic one4all DALI Driver (TD)
240V Remote Tridonic basicDIM Bluetooth Driver (TB)

Notes
¹ Flo horticulture series is only available in a 26W variation. Higher output options available upon request.
² For CRI 97+ lumen outputs, please refer to the values on the Unios Toolbox.

Spotlight Series

Accessories
 Honeycomb Lens
 Linear Lens

Product Collection
 Kobe Track Light Series Page 144

Beam Options
 Pencil 15° (P)
 Medium 36° (M)
 Wide 60° (W)