











Kobe

Track Light Series



8W	15W	26W	35W
Measurements (mm)	Measurements (mm)	Measurements (mm)	Measurements (mm)
 Ø 74 147	 Ø 74 160	 Ø 105 170	 Ø 105 188
Absolute Luminous Flux	Absolute Luminous Flux	Absolute Luminous Flux	Absolute Luminous Flux
8W (200mA) 735lm (at 3000K) 752lm (at 4000K)	15W (380mA) 1311lm (at 3000K) 1492lm (at 4000K)	26W (670mA) 2301lm (at 3000K) 2437lm (at 4000K)	35W (900mA) 3357lm (at 3000K) 3458lm (at 4000K)
Beam	Beam	Flo Horticulture¹	Beam
15° (P) 36° (M) 60° (W)	15° (P) 36° (M) 60° (W)	26W (700mA) 1815lm (at 2400K)	15° (P) 36° (M) 60° (W)
Weight	Weight	Beam	Weight
0.72kg	0.83kg	15° (P) 36° (M) 60° (W)	1.62kg
		Weight	
		1.26kg	

Finishes	
Textured Black	
White/Black Trim	
Black/Gold Trim	
White/Gold Trim	



General Specifications	
Material	Powder Coated Aluminium
Track Mount	Three (3C) Circuit, Single (1C) Circuit
UGR (Unified Glare Rating)	<13
IP	20
Warranty	5 Years




LED	
Colour Temp	2400K (Horticulture)¹, 3000K, 4000K
CRI (Ra/R9)	92+ />50
Efficacy	Up to 92lm/W
Colour Deviation	SDCM≤2
Lifetime	>55,000h L80B10
PPF (Flo series)	Typical (43.2 umol/sec)
Active-PPF (Flo series)	Typical (29.1 umol/sec)


Driver
240V Built-in Phase-Cut Dimmable Driver
240V Track Adaptor Gearbox Tridonic one4all DALI Driver (TD)
240V Track Adaptor Gearbox Tridonic basicDIM Bluetooth Driver (TB)

Notes
¹Flo horticulture series is only available in a 26W variation. Higher output options available upon request



Accessories

Linear Lens

Honeycomb Lens

Beam Options

Pencil 15° (P)

Medium 36° (M)

Wide 60° (W)

Product Collection

Kobe Spotlight Series Page 98